UROVO | Google Mobile Service

Industrial Mobile Computer

RT40



- Industrial grade condensation hardware. Equipped with heater of LCD/scan engine, and low temperature battery. Your cold chain solution.
- Hot-swap battery design, exchanges exhausted battery without reboot. Increase your efficiency.
- Qualcomm Octa-core 1.8GHz high-efficiency processor and cutting-edge Android Q operating system, gives you unparalleled performance.
- 38 keys island-style keyboard + 4" giant touch screen, intuitive operation reaction, accurate even with glove hands.
- Built-in industrial-leading scan engine, captures 1D/2D barcodes on screen and paper even if they are contaminated, wrinkled or distorted. 15m long-range version is optional.



IP68 Waterproof
1.8m Drop Resistance

Seamless Wi-Fi Roaming
4G Communication

13M Pixel
AF Camera

4" Touch Screen
Corning Gorilla glass

Working Temperature
-30°C~+50°C

UEE UROVO
Enterprise Enabler

RT40 Industrial Mobile Computer

Specifications

Processor
Octa-core 1.8GHz

O.S.
Android Q (10)

Memory
4GB RAM/ 64GB ROM,
microSD card,
Max.128GB extension

Screen
4 inch 480*800 pixel

Dimensions
199 x 58(handle) x29(thinnest)mm
(7.834 x 2.283 x 1.14 inch)

Cover glass
Corning Gorilla

Weight
425g

Main battery
3.85V 5200mAh,
Support battery swap,
exchange battery without
boot-up,Charging time: Less
than 3 hours.

Audio
Earpiece, speaker,
microphone Support PTT
(Push-to-Talk),
speaker loudness over
100dB at 10cm.

Scanner
Standard range scanner and
extended range scanner are optional
Support all industry-leading 1D/2D
barcode on paper or screen

Camera
Rear camera: 13M pixel
with flashlight.

Buttons
38 keys isolation keyboard

Bluetooth
Bluetooth 5.0
BR/EDR
BLE

Wi-Fi
iEEE 802.11 a/b/g/n/ac/d/e/
h/i/k/r/v/w 2.4GHz/5GHz

Sensor
Light sensor,
proximity sensor,
Accelerometer(optional)
e- compress(optional)
gyro sensor(optional)

Slot
Nano-SIM*2,
PSAM/ SIM*1
(self-adaption).

WWAN
4G, 3G, 2G

GNSS
GPS, Beidou,
GLONASS, Galileo

Sealing
IP68,
1.8m (5.9 ft.) flat concrete

Environment
Working temperature: -20°C ~ +50°C
(cold chain version -30°C ~ +50°C),
Storage temperature: -40°C ~ +70°C
(-40°F ~ +158°F), Humidity: 5%RH 95%RH
(non-condensing), ESD:±15kV air,
±8kV direct.

Urovo Technology Co., Ltd.

- Tel: 86 755-22673926 • Website: en.urovo.com • E-mail: urovo@urovo.com
- Address: Room 613,6/F.,Asia Trade Centre,79 Lei Muk Road,Kwai Chung,N.T.,Hong Kong

* This page is subject to change
without prior notice